


# D O O R S I L E N C E R S

No.	Description	Size	ANSI
500	Metal Frames	1/2" diameter x 9/16"	L03011
501	Wood Frames	3/8" x 3/4" x 11/16"	L03021



500



501


## Numbers 500 and 501

Door silencers are furnished in standard gray rubber. They are used to eliminate door rattles and absorb the shock of door closing.

# R O L L E R L A T C H E S



No.	Size	Strike	ANSI
550	1" x 3-3/8"	2-1/4" x 1-11/16"	E09091
550 x SP1	1" x 3-3/8"	2-3/4" x 1-1/8"	-
550 x SP2	1" x 3-3/8"	4-7/8" x 1-1/4"	-
553	1-1/8" x 2-1/4" x 1" Dia. Bore	2-3/4" x 1-1/8"	E19101
555	1-1/2" x 4-1/2" x 3/4"	2-1/4" x 1-1/8"	-




550




SP1



SP2



553



555

## Number 550

Forged brass heavy duty construction designed for use on interior doors. The projection of the roller is adjustable for various door clearances and latch pressure can be adjusted after installation. Designed to ANSI template specifications.

## Number 553


Designed to fit in a 1" diameter cylinder lock mortise. Standard strike is SP1. Optional strike is SP2.

## Number 555


Solid brass construction 3/16" thick angle face equipped with door silencers to provide a combination door stop and roller latch. Specified where frame stop strip is not required, can be installed on head frames or side jambs.

# A N G L E S T O P S


No.	Description	Size
556	Single Door	1" x 2" x 1-1/2"
557	Pair of Doors	1" x 2" x 3"



556



557



556/557 end view


## Numbers 556 and 557

Angle stops designed to be secured in the head of a cased opening.

# D O O R G U A R D



No.	Jamb Plate	Arm Length	Strike Plate	ANSI
580	2-5/8" x 1-1/32"	4-3/4"	1-3/4" x 1-1/16"	L03041



580

## Number 580

This security door guard allows the door to be opened slightly for viewing while maintaining security. It also comes standard with a 1" x 7/16" x 1-1/4" door edge protector.